

DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR**1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

Trade name	:	DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR		
Company	:	Dow Corning S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium		
Service	:	Dow Corning Central Europe	Tel: +49 6112371	
			Fax: +49 611237609	
		Dow Corning Northern Europe	Tel: +44 1676528000	
			Fax: +44 1676528001	
		Dow Corning Southern Europe	Tel: +33 472841360	
			Fax: +33 472841379	
Emergency Phone Number	:	Dow Corning (Barry U.K. 24h)	Tel: +44 1446732350	
		Dow Corning (Wiesbaden 24h)	Tel: +49 61122158	
		Dow Corning (Seneffe 24h)	Tel: +32 64 888240	
Use of the substance/preparation	:	Adhesive, binding agents		

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification
Triacetoxylethylsilane	17689-77-9	241-677-4	2.0	R14 R34 Xn R22
Methyltriacetoxysilane	4253-34-3	224-221-9	2.0	R14 R34 Xn R22

3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

4. FIRST AID MEASURES

On contact with eyes	:	Flush with water.
On skin contact	:	Flush with water.
If inhaled	:	Remove to fresh air.
On ingestion	:	No first aid should be needed.

DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR**5. FIRE FIGHTING MEASURES**

- Suitable extinguishing media** : Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- Hazards during fire fighting** : None known.
- Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.
- Hazardous Combustion Products** : Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Wear proper protective equipment.
- Precautions to protect the environment** : Do not allow large quantities to enter drains or surface waters.
- Methods for cleaning up** : Scrape up and place in a container fitted with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

- Advice on safe handling** : General ventilation is recommended. Local ventilation is recommended. Avoid skin and eye contact. Do not breathe vapour.
- Advice on storage** : Do not store with oxidizing agents. Keep container closed and store away from water or moisture.
- Specific uses** : Refer to technical data sheet available on request.
- Unsuitable packaging materials** : None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Engineering Controls** : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name	CAS-No.	Exposure Limits
------	---------	-----------------

DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR

Triacetoxy(ethyl)silane	17689-77-9	10 ppm TWA (CH ₃ COOH) 25 mg/m ³ TWA (CH ₃ COOH)
Methyltriacetoxy silane	4253-34-3	10 ppm TWA (CH ₃ COOH) 25 mg/m ³ TWA (CH ₃ COOH)

Personal protection equipment

Respiratory protection	:	Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded. A full-face mask is recommended. Recommended Filter type: AXE The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.
Hand protection	:	Chemical protective gloves should be worn: Silver shield(TM). 4H(TM). Regarding glove's breakthrough time...,contact your chemical protective glove supplier.
Eye protection	:	Safety glasses should be worn.
Skin protection	:	Protective equipment is not normally necessary.
Hygiene measures	:	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
Environmental exposure controls	:	Refer to section 6 and 12.
Additional information	:	These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Form: Paste **Colour:** Colorless **Odour:** Acetic acid

Important health, safety and environmental information

Explosive properties : No

Specific Gravity : 1.04

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR

Stability	:	Stable under normal usage conditions.
Conditions to avoid	:	None established.
Materials to avoid	:	Can react with strong oxidising agents. Cures in the presence of water or moisture, releasing a small amount of acetic acid.
Hazardous decomposition products	:	See section 11. If this product is heated to > 150 degrees C, trace quantities of formaldehyde may be released, and adequate ventilation is required.

11. TOXICOLOGICAL INFORMATION

On contact with eyes	:	Vapours released during curing may cause eye irritation.
On skin contact	:	Can irritate on prolonged or repeated contact.
If inhaled	:	The vapour is irritating to the mouth, nose and throat.
On ingestion	:	Small amounts transferred to the mouth by fingers during use should not injure. Swallowing large amounts may cause digestive discomfort.
Other Health Hazard Information	:	This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

Solid material, insoluble in water. No adverse effects are predicted.

Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDERATIONS

Product disposal	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
-------------------------	---	---

DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR

Packaging disposal : Dispose of in accordance with local regulations. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION**Road / Rail (ADR/RID)**

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION**Labelling according to EEC Directive**

S-phrases : S24 Avoid contact with skin.
S51 Use only in well-ventilated areas.

National legislation / regulations

Ozone depleting chemicals : No ozone depleting chemicals are present or used in manufacture.

Status

EINECS : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DOW CORNING(R) 786 SILICONE SEALANT - M CLEAR**16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R14 Reacts violently with water., **R22** Harmful if swallowed., **R34** Causes burns.