

TECHNICAL DATASHEET

ALPHA GRIP

Description & Uses

ALPHA GRIP is a high quality, multi-purpose, fast bonding grab adhesive also ideal for gap filling. This solvent based adhesive is the perfect replacement for mechanical fixings in a wide variety of applications whether internal or external with excellent creep and slump resistance. Ideal for fixing skirting boards, wall battens, gripper rods, laminates and much more, suitable for use on porous and rough substrates.

ALPHA GRIP truly is multi-purpose, working on a wide variety of building materials including aluminium, brick, steel, stone, concrete, wood, chipboard, plasterboard, tiles, PVCu cladding and building panels. It can be used in interior and exterior applications.

Directions

- Ensure all surfaces are clean, sound, dry and free from dust, grease or other contaminants.
- Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed.
- Insert a screw driver into the nozzle to pierce the centre of the membrane.
- Apply a 6mm bead (or thicker to suit gap) to one surface, the length of the material and press onto the second surface applying even pressure. Allow to set.
- Excess adhesive should be removed with white spirit.
- Temporary support or fixings are recommended on very heavy items whilst curing.
- Full strength is achieved in 24-48 hours.
- It is the user's responsibility to dispose of all packaging correctly.

Storage

Store in cool, dry conditions below 30° in well ventilated conditions. Store in accordance with flammable storage regulations.

If spillages occur remove all sources of ignition and ventilate the area – ensure people are removed from confined areas. Product should be cleaned up immediately with an inert and absorbent material, i.e. sawdust or sand and collected using non-sparking tools.

Shelf Life

24 months when stored in original, unopened packaging.

Limitations

- Not suitable for areas subject to frequent water immersion.
- Not recommended for use on asphalt, bitumen or polystyrene.



- Not to be used as a mirror adhesive.
- Dusty or porous surfaces should be primed prior to application of adhesive.
- It is the user's responsibility to ensure suitability for use.
- Read the label carefully for essential health and safety information prior to use.

Please Note – extremely flammable – please refer to SDS for full details.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.